

**ECONODRAIN<sup>®</sup> #8 & PT-2 #8 SYSTEM - HYDRAULIC DATA**

Standard Depth & Slope <sup>1</sup>			Radius Bottom Trench (Std.)				Rectangular Trench (Optional Custom)			
EPS Form Number	[Slope [S <sub>t</sub> ] = 0.5% or 0.005 ft/ft]		Q <sub>max</sub> <sup>2</sup> Flow (cfs)	Q <sub>max</sub> <sup>2</sup> Flow (gpm)	(F <sub>k</sub> is not a Flow Rate)		Q <sub>max</sub> <sup>2</sup> Flow (cfs)	Q <sub>max</sub> <sup>2</sup> Flow (gpm)	(F <sub>k</sub> is not a Flow Rate)	
	Min. (in)	Max. (in)			F <sub>k</sub> <sup>3</sup> (cfs)	F <sub>k</sub> <sup>3</sup> (gpm)			F <sub>k</sub> <sup>3</sup> (cfs)	F <sub>k</sub> <sup>3</sup> (gpm)
0806	6	6 1/2	0.63	281	8.68	3,895	0.74	334	10.32	4,630
0807	6 1/2	7	0.72	325	10.04	4,506	0.84	378	11.66	5,235
0808	7	7 1/2	0.82	370	11.42	5,126	0.94	422	13.03	5,848
0809	7 1/2	8	0.93	415	12.82	5,755	1.04	467	14.41	6,469
0810	8	8 1/2	1.03	461	14.24	6,389	1.14	512	15.81	7,096
0811	8 1/2	9	1.13	507	15.66	7,029	1.24	558	17.22	7,728
0812	9	9 1/2	1.23	554	17.10	7,674	1.35	604	18.64	8,365
0813	9 1/2	10	1.34	601	18.54	8,322	1.45	650	20.07	9,006
0814	10	10 1/2	1.44	648	19.99	8,974	1.55	696	21.50	9,651
0815	10 1/2	11	1.55	695	21.45	9,629	1.66	743	22.94	10,298
0816	11	11 1/2	1.65	742	22.92	10,287	1.76	790	24.39	10,949
0817	11 1/2	12	1.76	790	24.39	10,946	1.87	837	25.85	11,601
0818	12	12 1/2	1.87	838	25.86	11,608	1.97	885	27.31	12,257
0819	12 1/2	13	1.97	886	27.34	12,271	2.08	932	28.77	12,914
0820	13	13 1/2	2.08	934	28.82	12,936	2.18	980	30.24	13,573
0821	13 1/2	14	2.19	982	30.31	13,602	2.29	1027	31.71	14,233
0822	14	14 1/2	2.29	1030	31.79	14,270	2.40	1075	33.19	14,895
0823	14 1/2	15	2.40	1078	33.28	14,939	2.50	1123	34.66	15,559
0824	15	15 1/2	2.51	1126	34.78	15,609	2.61	1171	36.15	16,223
0825	15 1/2	16	2.62	1175	36.27	16,279	2.72	1219	37.63	16,889
0826	16	16 1/2	2.73	1223	37.77	16,951	2.82	1267	39.11	17,556
0827	16 1/2	17	2.83	1272	39.26	17,623	2.93	1315	40.60	18,224
0828	17	17 1/2	2.94	1320	40.76	18,296	3.04	1363	42.09	18,892
0829	17 1/2	18	3.05	1369	42.27	18,970	3.15	1412	43.58	19,562
0830	18	18 1/2	3.16	1418	43.77	19,644	3.25	1460	45.08	20,232
0831	18 1/2	19	3.27	1466	45.27	20,319	3.36	1509	46.57	20,903
0832	19	19 1/2	3.38	1515	46.78	20,994	3.47	1557	48.07	21,575
0833	19 1/2	20	3.48	1564	48.28	21,670	3.58	1606	49.57	22,247
0834	20	20 1/2	3.59	1613	49.79	22,347	3.69	1654	51.07	22,920
0835	20 1/2	21	3.70	1662	51.30	23,023	3.79	1703	52.57	23,593
0836	21	21 1/2	3.81	1710	52.80	23,700	3.90	1751	54.07	24,267
0837	21 1/2	22	3.92	1759	54.31	24,378	4.01	1800	55.57	24,941
0838	22	22 1/2	4.03	1808	55.82	25,056	4.12	1849	57.07	25,616
0839	22 1/2	23	4.14	1857	57.33	25,734	4.23	1897	58.58	26,291
0840	23	23 1/2	4.25	1906	58.85	26,412	4.34	1946	60.08	26,967
0841	23 1/2	24	4.36	1955	60.36	27,091	4.44	1995	61.59	27,643
0842	24	24 1/2	4.47	2004	61.87	27,770	4.55	2044	63.10	28,319
0843	24 1/2	25	4.57	2053	63.38	28,449	4.66	2093	64.60	28,996
0844	25	25 1/2	4.68	2102	64.90	29,128	4.77	2141	66.11	29,673
0845	25 1/2	26	4.79	2151	66.41	29,808	4.88	2190	67.62	30,350

- Standard Depth is measured from the top of the grate rail to the trench invert.
- Q<sub>max</sub> is based on Manning's Equation n = 0.13 and S<sub>t</sub> = 0.5%. The outlet end depth flow area is utilized and the grate area is excluded. The flow values shown do not include site grade slope.
- F<sub>k</sub> is used to include site grade slope in trench flow calculations. The equation is: Flow, Q = F<sub>k</sub> × (S<sub>s</sub> + S<sub>t</sub>)<sup>1/2</sup> where S<sub>s</sub> is the site slope and S<sub>t</sub> is the trench form slope (ft/ft), (dimensionless).

**MultiDrain Systems, Inc.**  
1405 Industrial Drive • Statesville, NC 28625 • (704) 508-1010 • (800) 433-1119 • Fax (704) 508-1011 • md.multidrainsystems.com

"DISCLAIMER: The customer and the customer's architects, engineers, consultants and other professionals are completely responsible for the selection, installation, and maintenance of any product purchased from MULTIDRAIN SYSTEMS, INC., and EXCEPT AS EXPRESSLY PROVIDED IN MULTIDRAIN'S STANDARD WARRANTIES, MULTIDRAIN MAKES NO WARRANTY, EXPRESS OR IMPLIED, AS TO THE SUITABILITY, DESIGN, MERCHANTABILITY, OR FITNESS OF THE PRODUCT FOR CUSTOMER'S APPLICATION. Copies of MultiDrain's standard warranties are available upon request."